# **UK** Declaration of Performance

# 1. Unique Identification Code of the Product Type

Lime Green Coloured Cement Mortars - Class I, Class II, Class III and Class IV

#### 2. Intended Use

General Purpose Mortar for external use in masonry wall, columns and partitions

## 3. Name and contact address of the Manufacturer

Lime Green Products Ltd, Coates Kilns, Stretton Road, Much Wenlock, Shropshire, TF13 6DG

## 4. Authorised Representative

N/a

## 5. System of Assessment

System 4

#### 6. Harmonised Standard

EN BS 998-2 2016

#### 7. Declared Performance

Essential Characteristics	Performance				Harmonised
	Class i	Class ii	Class iii	Class iv	Technical Specification
Proportion of constituents (Volume) Cement Lime Sand	1 0.25 3	1 0.5 4.5	1 1 6	1 2 9	National Annex EN998-2
Content of Chlorides	<0.1%	<0.1%	<0.1%	<0.1%	
Reaction to Fire	A1	A1	A1	A1	
Water absorption	0.8kg/(m <sup>2</sup> .min <sup>0.5</sup> )	0.8kg/(m <sup>2</sup> .min <sup>0.5</sup> )	1.0kg/(m <sup>2</sup> .min <sup>0.5</sup> )	1.0kg/(m².min <sup>0.5</sup> )	
Water Vapour Permeability	15/35	15/35	15/35	15/35	EN998-2 2016
Thermal Conductivity	0.82W(m.K)	0.82W(m.K)	0.82W(m.K)	0.82W(m.K)	
Durability	As per recommendations in the NA of Eurocode 6				
Dangerous Substances	See SDS				

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued in accordance with Construction Products Regulation 2011 as retained in UK law, under the sole responsibility of the manufacturer identified above

# Signed for and on behalf of the manufacturer

James Ayres Director

23/11/22