

Declaration of Performance

1. Unique identification code of the product-type: Lime Green Natural Lime Mortar: Strong
2. Intended use or uses: Prescribed general purpose masonry mortar for internal and external use.
3. Manufacturer: Lime Green Products Ltd
Coates Kilns
Stretton Road
Much Wenlock
Shropshire
TF13 6DG
4. Authorised representative: N/A
5. System/s of AVCP: System 4
6. Designated / Harmonised standard: EN 998-2
7. Declared performance/s:

Essential characteristics	Performance	Designated technical specification
Proportion of constituents	2 ½ : 1 Sand to NHL5 lime	EN 998-2
Reaction to Fire	A1	
Water Absorption	0.69 [kg/(m ² ·min ^{0.5})]	
Water Vapour Permeability	15/35	
Thermal Conductivity	0.61	
Durability	NPD	
Dangerous Substances	None	

8. Appropriate Technical Documentation and/or Specific Technical Documentation: N/A.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

James Ayres



Director: Much Wenlock 9/10/2026



Lime Green Products Limited,
Coates Kilns,
Stretton Road
Much Wenlock
Shropshire
TF13 6DG

26

EN 998-2: 2016

Prescribed general purpose masonry mortar for internal and external use

Proportion of constituents	2 ½ : 1 Sand to NHL5 lime
Reaction to Fire	Class A1
Water Absorption	0.69 [kg/(m ² ·min ^{0.5})]
Water Vapour Permeability	μ 15/35
Thermal Conductivity	(λ _{10.dry}) 0.61 W/mK (tab. mean value; P = 50%)
Durability	NPD
Dangerous Substances	None